



## Product Specification

Product Name: **PORTER'S LIQUID STAINLESS STEEL**

---

### PRODUCT DESCRIPTION:

Porter's Liquid Stainless Steel is an easy to use water-based paint that is designed to give an authentic sleek, stylish stainless steel effect. Liquid Stainless Steel adds warmth, purity and urban chic to any décor and looks simply stunning when used in combination with other textures, such as timber or tiles. Liquid Stainless Steel contains genuine stainless steel flake.

### LOCATION:

Interior and exterior.

### ENVIRONMENTAL INFORMATION:

This product contains: 92g/L VOC.

APAS\* Target level for this product: 450g/L.

Although this product is unique and there is no comparative product type, the closest comparison would be a typical oil-based micaceous paint that has a VOC level of approx. 350-450g/L

Porter's Paints use only premium grade, low odour, minimal environmental impact raw

materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

\* Australian Paint Approval Scheme.

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry, metal and previously painted surfaces.

### COLOUR:

Light silvery grey. Available in one colour only.

### LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

### PREPARATION:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould.

Previously painted surfaces should be sanded to remove gloss and create a "keyed" surface. Dust down before proceeding. Spot prime all joints and repaired areas with Porter's Universal Primer, then apply two coats of same to entire area. Touch dry 2 hours. Allow 6 hours dry time between coats and 24 hours dry time prior to the application of Liquid Stainless Steel.

#### **APPLICATION:**

Stir thoroughly prior to use with a broad spatula or a drill with a paint mixing attachment to ensure even distribution of the stainless steel particles.. Apply one coat by brush or spray. On broad wall areas application by spray is recommended as this will give a more authentic appearance to the stainless steel finish. On smaller areas where spraying is not an option, use a brush. Best results are achieved by laying off or reworking paint to achieve a brushed stainless steel effect. Touch dry in 30 minutes. Allow minimum 3 hours dry time between coats. If correctly applied, no second coat is required.

#### **COVERAGE RATES:**

Covers approximately 12-14m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

#### **WASH UP:**

Water.

#### **COMPLEMENTARY PRODUCTS:**

Porter's Universal Primer (coverage 10m<sup>2</sup> per litre) is recommended where an undercoat/primer is required when preparing substrate for painting.

#### **PACKAGING:**

Porter's Stainless Steel is available in 250ml & 1 litre sizes.

#### **STORAGE:**

Store in a cool dry area, protected from frost.

#### **PRECAUTIONS:**

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

#### **WARRANTY:**

Porter's Liquid Stainless Steel has a warranty of 7 years. Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

## MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd  
895 Bourke St  
Waterloo NSW 2017  
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)

Web: [www.porterspains.com](http://www.porterspains.com)