



## Product Specification

Product Name:

# PORTER'S WALLPAPER

---

### PRODUCT DESCRIPTION:

Porter's has collaborated with local designers to create beautiful works that translate into stunning wallpaper. We have produced a selection of wallpapers that will satisfy both the contemporary and traditional interior spaces. With inspiration coming from nature, historical references and innovative modern form, we have produced a selection of ranges for any style of home. Our bold designs and beautiful colours are unique and have been carefully selected to inspire you. Porter's paper is printed locally by specialized staff on our own wallpaper press using premium quality paper.

### LOCATION:

Interior.

### ENVIRONMENTAL INFORMATION:

Porter's Wallpaper Paste contains: 0g/L VOC.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint

formulations are designed for maximum performance with minimum impact on user health.

Our paper is sourced locally, but originates from European timber plantations.

### SUGGESTED APPLICATIONS:

Can be applied to most interior surfaces including set plaster and plasterboard, MDF and most smooth interior surfaces.

### COLOURS AND CUSTOM COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

Whilst we know you will love the colour combinations we have designed for our wallpaper range, we understand that sometimes you would like to create your own colour palette to suit your interiors. The skilled colourists at Porter's have the ability to match any colour you wish and create custom wallpapers to your specifications. Minimum purchase 10 rolls and set up costs may apply.

All current wallpaper designs offered by Porter's Paints can also be custom-matched to client

colour requirements, using a Porter's fandeck or Pantone colour reference (preferably uncoated). Colour changes to the Designers designs require approval from the designer. There is a set up fee for new colours this includes; ink colours, colour matching and a strike off sample.

## **DESIGNS AND BESPOKE DESIGNS:**

We have a wide selection of designs, and Porter's also offer a bespoke wallpaper design service for architects and designers. Simply produce a design meeting Porter's technical requirements and watch as we transform it into a stunning wallpaper. **Minimum** order of 10 rolls and set up costs apply.

## **SET UP COSTS:**

A pass-on cost for the production of plates and/or print rollers is charged for initial orders of custom wallpaper, which varies according to the complexity of the design. These costs can vary from \$500 to \$2000 depending on the required design. Successive orders do not attract this set-up cost.

A detailed quote and lead-time indicator will be provided upon receipt of a PDF or EPS of the design.

Production on any custom wallpaper designs will not commence without written confirmation or purchase order from the customer.

## **ARTWORK REQUIREMENTS:**

All artwork for custom wallpaper designs needs to be submitted on a template supplied by Porter's wallpaper designer, on request. The artwork needs to be in Illustrator (EPS) format. Using a Porter's fandeck or Pantone colour reference

(preferably uncoated) to indicate selected colours for print.

## **BASIC MEASUREMENTS:**

All Porter's Paints Wallpaper is supplied in 10.5m rolls x 530mm wide. Repeats need to be 609.6mm.

Lead-time for custom wallpaper orders is four weeks from time of receipt of signed purchase order.

## **LIMITATIONS:**

Do not apply in high humidity, below 10°C or above 30°C.

## **PREPARATION:**

To ensure consistency of colour and pattern check each roll of wallpaper and make certain that all rolls are the same batch number.

Walls should be prepared, clean, dry and smooth. Fill any cracks or nail holes, remove loose paint or plaster and repair. All walls should either be painted or have a glue size applied to enable slipping and to avoid paste being absorbed (paper may not adhere if this occurs) prior to painting.

## **APPLICATION:**

### **PASTING PAPER:**

Step 1:

With a utility knife cut a length of paper about 10cm longer than the wall, although with a large repeating pattern you may have to cut longer pieces to ensure the pattern matches up.

#### Step2:

Apply an even coat of paste over entire back surface of paper, ensuring edges are well pasted. Avoid getting paste on the front surface. Fold each end of the paper to meet in the middle (a process called "booking") then allow it to relax. It may take between 5 to 15 minutes to soften, depending on air temperature. Do not overlap the paper.

#### HANGING PAPER:

##### Step 1:

To ensure that paper is hung level, always check to find the most level area to start papering. Use a spirit level or plumb bob to find a straight start point.

##### Step 2:

Smooth paper from centre to edge with a smoothing brush to remove bubbles.

##### Step 3:

Trim top and bottom using a sharp utility knife. Use a straight edge as a guide.

##### Step 4:

Continue as above with next piece. After Step 2, roll each seam with a seam roller, taking care not to squeeze out the paste. Using a damp cloth with clean water, wipe off any paste on the surface of the paper.

#### COVERAGE RATES:

Approximately 5.2 cubic metres (56 square feet) per roll. As a guide, 1 roll is approximately 3 drops in a room with average ceiling height. Coverage can vary due to pattern matching, wastage etc.

#### COMPLEMENTARY PRODUCTS:

Porter's Wallpaper Paste is recommended for use when applying Porter's wallpapers. Coverage, approximately 1kg per roll.

#### TECHNICAL SPECIFICATIONS:

Light fast pigments and a protective vinyl lacquer overlay. Washable matt finish. Pre-trimmed to a standard English roll width (53cm) and length (10.5m).

Complies with Australian Standard 1530 for Early Fire Hazard Properties.

	<u>Range 0-20</u>
Ignitability	14
Heat evolved	1
Spread of flame	0
Smoke developed	3

#### STORAGE:

Store in a cool dry area, protected from moisture and frost.

#### PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

#### WARRANTY:

Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied

here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

#### **MANUFACTURER'S/DISTRIBUTOR'S DETAILS:**

Porter's Paints Pty Ltd  
895 Bourke St  
Waterloo NSW 2017  
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)

Web: [www.porterspains.com](http://www.porterspains.com)