



## Product Specification

Product Name:

# PORTER'S WOOD WASH

---

### PRODUCT DESCRIPTION:

Porter's Wood Wash is a translucent coating that subtly softens and ages the appearance of bare timber, highlighting the grain and replicating the look of limed timber. Wood Wash is supplied as a neutral white base that can be tinted to any colour.

### LOCATION:

Interior.

### ENVIRONMENTAL INFORMATION:

This product contains: 50g/L VOC.

APAS\* Target level for this product: 70g/L.

Although this product is unique and there is no comparative product type, the closest comparison would be a typical water-based flat paint that has a VOC level of approx. 70g/L

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint

formulations are designed for maximum performance with minimum impact on user health.

\* Australian Paint Approval Scheme.

### SUGGESTED APPLICATIONS:

Can be applied to most bare timber furniture, floorboards, lining boards or timber trim.

### COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

### LIMITATIONS:

Not suitable for use over some tannin rich timbers, such as Western Red Cedar. Always test prior to use. Do not apply in high humidity, below 10°C or above 30°C.

### PREPARATION:

Substrate should be sanded to expose clean bare timber free from paint, dirt, grease, oil and previous coatings. Dust down before proceeding.

## APPLICATION:

Stir thoroughly prior to use.

*First coat* – apply Porter's Wood Wash by brush or lamb's wool applicator, following the grain of the timber. Within 3-4 minutes wipe off excess Wood Wash with muslin or lint-free cloth to achieve desired pattern and depth of colour. Touch dry 2-4 hours. Allow to dry for 24 hours.

*Second coat (for a more opaque effect - optional)* – Allow first coat to dry for 24 hours then apply a second coat as per first coat. Allow 24 hours dry time.

## COVERAGE RATES:

Covers approximately 20m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

## WASH UP:

Water.

## COMPLEMENTARY PRODUCTS:

Porter's Wood Wash can be sealed and protected with Porter's Clearcote (coverage 15m<sup>2</sup> per litre). Allow Wood Wash to dry for 72 hours before applying Clearcote. Test before use as a slight colour variation may occur.

## PACKAGING:

Porter's Wood Wash is available in 500ml, 1 litre, 4 litre & 15 litre sizes.

## STORAGE:

Store in a cool dry area, protected from frost.

## PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

## WARRANTY:

Porter's Wood Wash has a warranty of 7 years. Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

## MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd  
895 Bourke St  
Waterloo NSW 2017  
Australia

Phone: (02) 9698-5322  
Toll free: 1800 656 664  
Fax: (02) 9699-5322  
E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)  
Web: [www.porterspains.com](http://www.porterspains.com)