



Product Specification

Product Name: **PORTER'S ALL PURPOSE CLEAR SEALER**

PRODUCT DESCRIPTION:

Porter's All Purpose Clear Sealer is an interior use sealer that is suitable for floors, walls and furniture and is the only clear sealer recommended as a protective clear sealer for use over Porter's Milk Paint and Porter's Fresco. It is quick drying with superior resistance to yellowing. Dries to a beautiful satin finish. Although All Purpose Clear Sealer is suitable for floors, we would recommend Porter's Clearcote as a better choice on floors, as it is much stronger and designed specifically for this use.

LOCATION:

Interior.

ENVIRONMENTAL INFORMATION:

This product contains: 34g/L VOC.

APAS* Target level for this product: 60g/L.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing

processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared interior timber, floors and furniture. Suitable for use as a protective clear sealer for use over Porter's Milk Paint and Porter's Fresco.

COLOUR:

Appears milky white in can, dries clear.

LIMITATIONS:

Not suitable for use over previously oiled timbers. Test before use on timber with a high tannin content. Normally tannin bleed is undetectable, but if you are using All Purpose Clear Sealer over a finish such as Wood Wash or Milk Paint tannin bleed may be visible as a slight brown staining. Tannin bleed does not affect product performance.

Not suitable for use in wet areas.

Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould. Dust down before proceeding. Allow all paints and finishes to a dry a minimum of 72 hours prior to the application of Porter's All Purpose Clear Sealer. When being applied as a floor sealer, vacuum prior to application.

APPLICATION:

Stir thoroughly prior to use. Apply 2 to 3 coats by brush, or lambs' wool applicator (recommended for floors). Touch dry in 2 hours. Allow minimum 12 hours dry time between coats. Sand lightly between coats to remove any raised grain. Vacuum to remove dust before applying another coat. Allow 24 hours before allowing light foot traffic on floor surfaces. Full cure is achieved in 7 days.

COVERAGE RATES:

Covers approximately 15m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's All Purpose Clear Sealer is compatible for use over Porter's Milk Paint and Porter's Fresco. Test before use as a slight colour variation may occur.

PACKAGING:

Porter's All Purpose Clear Sealer is available in 1 litre, 4 litre & 15 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

WARRANTY:

Porter's All Purpose Clear Sealer has a warranty of 7 years. Porter's Paints Pty Ltd warrants this product to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com