



Product Specification

Product Name: **PORTER'S CEMENT CRACK SEALER**

PRODUCT DESCRIPTION:

Porter's Cement Crack Sealer is for use prior to painting over new cement render or bagging that shows non-structural hairline cracking. Designed to bridge cracks up to 0.3mm. Remains flexible throughout its life.

LOCATION:

Exterior

ENVIRONMENTAL INFORMATION:

This product contains: 0g/L VOC.

APAS* Target level for this product: 60g/L.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

CHECKING FOR HAIRLINE CRACKING:

Cement renders are occasionally subject to hairline cracking (caused by drying too fast). To test for hairline cracking hose down the cement render/bagging, and as it dries any cracks in the cement rendered surface will become evident.

SUGGESTED APPLICATIONS:

For use, prior to painting, over new cement render or bagging that shows non-structural hairline cracking.

COLOUR:

Appears milky white in can, dries clear.

LIMITATIONS:

Not suitable for use over previously painted surfaces. This product is designed for use under Boncote Cement Paint only. Contact Porter's Technical Department for advice on surface preparation over hairline cracking when using other paint types. Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

The substrate should be a clean well-held surface free from loose material dirt, dust, grease, oil and mould. Allow rendered or bagged surfaces to cure for a minimum of 28 days prior to application.

APPLICATION:

Stir thoroughly prior to use. Apply one coat by brush or roller to entire wall surface, edge to edge. Allow to dry overnight. Remains tacky until top coated.

COVERAGE RATES:

Covers approximately 12-14m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Cement Crack Sealer is suitable for use prior to painting with Boncote Cement Paint only.

PACKAGING:

Porter's Cement Crack Sealer is available in 1 litre & 4 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

WARRANTY:

Porter's Cement Crack Sealer has a warranty of 7 years. Porter's Paints Pty Ltd warrants this product to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com