



Product Specification

Product Name: **PORTER'S LIMEPROOF UNDERCOAT SEALER**

PRODUCT DESCRIPTION:

Porter's Limeproof Undercoat Sealer is an exterior/interior use undercoat primer/sealer that can be applied to bare paintable surfaces as an undercoat sealer, or for use over previously painted surfaces as an undercoat primer prior to the application of any Porter's paint or finish. White in colour. Ultra matt finish.

LOCATION:

Interior or exterior.

ENVIRONMENTAL INFORMATION:

This product contains: 15g/L VOC.

APAS* Target level for this product: 450g/L.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared interior or exterior surfaces, including timber, masonry, plaster board, timber, PVC piping and furniture.

COLOUR:

Porter's Limeproof Undercoat Sealer is supplied white. May be tinted if required.

LIMITATIONS:

Not suitable over new/bare set plaster. Not suitable for use over previously oiled timbers. Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould.

Newly completed walls should be left to cure before the application of Porter's Limeproof Undercoat Sealer. Minimum drying/curing times:

Cement render	28 days
Cement "bagged" surface	14 days
Bricks and mortar	56 days
Filled concrete blocks	56 days
Pre-cast and in-situ concrete	56 days

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

APPLICATION:

Stir thoroughly prior to use. Apply one or two coats by brush, medium nap roller or spray. Touch dry in 1 hour. Allow minimum 6 hours dry time between coats. Allow 6 hours dry time before over-coating.

Spray details (recommended by Wagner):
Tip size: 24thou. Filter: Green

COVERAGE RATES:

Covers approximately 12m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

PACKAGING:

Porter's Limeproof Undercoat Sealer is available in 1 litre, 4 litre, 10 litre & 15 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

WARRANTY:

Porter's Limeproof Undercoat Sealer has a warranty of 15 years. Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia

Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: www.porterspains.com