



## Product Specification

Product Name:

**PORTER'S MATT WALL SEALER**

---

### PRODUCT DESCRIPTION:

Porter's Matt Wall Sealer is an interior use product that is recommended as a protective clear sealer specifically designed for use over Porter's Interno, Porter's Interior Distemper, Porter's Lime Wash or Boncote Cement Paint (when used on a interior surface). Allows these surfaces to resist marking and staining, makes these matt decorative finishes wipeable.

When recoating Interno or Distemper that has been protected with Matt Wall Sealer, Matt Wall Sealer can be painted over directly without the need to begin again with an undercoat.

### LOCATION:

Interior.

### ENVIRONMENTAL INFORMATION:

This product contains: 7g/L VOC.

APAS\* Target level for this product: 75g/L.

Although this product is unique and there is no comparative product type, the closest comparison

would be a typical water-based interior low sheen paint that has a VOC level of approx. 75g/L

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

\* Australian Paint Approval Scheme.

### SUGGESTED APPLICATIONS:

Suitable for use as a protective clear sealer for use over Porter's Interno, Interior Distemper, Porter's Lime Wash and Boncote Cement Paint (interior) only.

### COLOUR:

Appears milky white in can, dries clear.

### LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C. Allow paints to cure for a minimum of

7 days before application. Over saturation whilst applying Matt Wall Sealer, or a substrate which is not completely dry, may cause white markings to appear on a surface. Avoid dribbles or runs as these will remain evident when dry. Test before use as a slight colour variation may occur.

#### **PREPARATION:**

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould. Dust down before proceeding. Allow all paints and finishes to a dry a minimum of 7 days prior to the application of Porter's Matt Wall Sealer.

#### **APPLICATION:**

Stir thoroughly prior to use. Apply two coats by brush in a random or "crows feet" method. Touch dry in 2 hours. Allow minimum 6 hours dry time between coats. Allow to dry 6 hours.

#### **COVERAGE RATES:**

Covers approximately 15m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

#### **WASH UP:**

Water.

#### **PACKAGING:**

Porter's Matt Wall Sealer is available in 1 litre, 4 litre & 15 litre sizes.

#### **STORAGE:**

Store in a cool dry area, protected from frost.

#### **PRECAUTIONS:**

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

#### **WARRANTY:**

Porter's Matt Wall Sealer has a warranty for 7 years. Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

#### **MANUFACTURER'S/DISTRIBUTOR'S DETAILS:**

Porter's Paints Pty Ltd  
895 Bourke St  
Waterloo NSW 2017  
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)

Web: [www.porterspains.com](http://www.porterspains.com)