



Product Specification

Product Name:

PORTER'S NATURAL TIMBER OIL

PRODUCT DESCRIPTION:

Porter's Natural Timber Oil is a clear, natural oil coating and preservative and sealer for bare timber. Will preserve and protect all interior and exterior woodwork from weather and rot while enhancing the timber's natural beauty and grain. Dries to a non-sticky finish with a slight lustre.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: 0g/L VOC.

APAS* Target level for this product: 450g/L.

Although this product is unique and there is no comparative product type, the closest comparison would be a typical ranch finish for exterior timber that has a VOC level of approx. 450g/L

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing

processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Recommended for use on exterior decking areas, timber balustrading, window frames and garden furniture. May be used on interior timber surfaces, although this product is not recommended on interior floors. May be used over previously oiled timbers that require a fresh coat.

MAINTENANCE:

Reapply 1 coat every 3-12 months, depending upon exposure and situation.

COLOUR:

Appears a clear honey colour in can, dries clear.

LIMITATIONS:

Not suitable for use over previously painted timbers. Do not overload surface with product. Allowing Natural Timber Oil to build up on

surfaces does not offer extra protection, and may result in stickiness/tackiness and dirt and dust build up. Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

Sand surface of timber before application for a more even result. Timber should be dry and free of contaminants. Where exterior hardwood timber has weathered and turned silver/grey, this must be sanded back to reveal the tannin rich new timber. On previously painted surfaces ALL paint must be removed and surface stripped bare and thoroughly sanded before application. Dust down surfaces prior to application. When being applied as a floor sealer, vacuum prior to application.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush or lambs' wool applicator (recommended for floors). Touch dry in 4 hours. Allow minimum 12 hours dry time between coats. Allow 24 hours before allowing foot traffic on floor surfaces.

COVERAGE RATES:

Covers approximately 12m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Warm water and mild detergent.

PACKAGING:

Porter's Natural Timber Oil is available in 1 litre & 4 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

WARRANTY:

Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com