



## Product Specification

Product Name:

**PORTER'S AQUA GLOSS ENAMEL**

---

### PRODUCT DESCRIPTION:

Porter's Aqua Gloss Enamel is a water based acrylic enamel that dries to a super shiny, extremely hardwearing finish that provides all the benefits of an oil based enamel with none of the drawbacks. Self leveling (eliminates brush marks), non-yellowing, tough wearing, long lasting with excellent gloss retention, easy to apply, low odour, low VOC, fast drying with easy re-coat. Excellent for exterior woodwork and trim areas as its high UV resistance ensures durability and longevity in extremes of temperature and climatic conditions. Porter's Aqua Gloss Enamel resists peeling and flaking and is fully washable.

### LOCATION:

Interior and exterior. Ideal for doors, architraves, windows and trim.

### ENVIRONMENTAL INFORMATION:

This product contains: av. 77g/L VOC.

APAS\* Target level for this product: 80g/L.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw

materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

\* Australian Paint Approval Scheme.

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, metal, wood, masonry and previously painted surfaces.

### COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

### LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

## **PREPARATION:**

### **NEW/UNPAINTED SUBSTRATES:**

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding. On bare surfaces such as new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Porter's Universal Primer, then apply one coat of same to entire area. Touch dry 2 hours. Allow 6 hours dry time between coats and 24 hours dry time prior to the application of Aqua Gloss Enamel.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Universal Primer. Touch dry 2 hours. Allow 6 hours dry time between coats and 24 hours dry time prior to the application of Aqua Gloss Enamel.

### **PREVIOUSLY PAINTED SUBTRATES:**

When painting over a water-based acrylic paint, provided the surface is clean, sound and sanded to remove gloss, Porter's Aqua Gloss Enamel is self-priming and can be applied direct. All varnishes, polyurethanes or surfaces previously painted with oil-based enamel paint should be thoroughly sanded to remove gloss and to create a "keyed" surface. Loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Universal Primer, then apply one coat of same to entire area.

Touch dry 2 hours. Allow 6 hours dry time between coats and 24 hours dry time prior to the application of Aqua Gloss Enamel.

## **APPLICATION:**

Stir thoroughly prior to use. Apply two coats by brush, short nap roller or spray. Touch dry in 1 hour. Allow minimum 3 hours dry time between coats. Allow 8 hours dry time.

## **COVERAGE RATES:**

Covers approximately 12-14m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

## **WASH UP:**

Water.

## **COMPLEMENTARY PRODUCTS:**

Porter's Universal Primer (coverage 10m<sup>2</sup> per litre) is also recommended. Gives a smoother overall result.

Mineral Silicate Primer (coverage 10m<sup>2</sup> per litre) is recommended for priming new set plaster before undercoating.

## **PACKAGING:**

Porter's Aqua Gloss Enamel is available in 1 litre & 4 litre sizes.

## **STORAGE:**

Store in a cool dry area, protected from frost.

## **PRECAUTIONS:**

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

## **WARRANTY:**

Porter's Aqua Gloss Enamel has a warranty of 15 years. Porter's Paints Pty Ltd warrants this product to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

## **MANUFACTURER'S/DISTRIBUTOR'S DETAILS:**

Porter's Paints Pty Ltd

895 Bourke St

Waterloo NSW 2017

Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)

Web: [www.porterspains.com](http://www.porterspains.com)