



Product Specification:

PORTER'S EGGSHELL FINISH

PRODUCT DESCRIPTION:

Porter's Eggshell Finish is a superior quality acrylic paint that gives walls and other surfaces a low reflective finish with an elegant, matt sheen level that maximises depth of colour. This chic finish is fully washable for interiors and highly durable for exteriors (see Warranty information at the end of this document). Fast drying with low odour.

Porter's Eggshell Finish is certified with the Global GreenTag GreenRate™ Level A. The Global GreenTag GreenRate™ Level A Certification is the highest ranking level in the GreenRate product certification program. This means that the product is not only beautiful and durable as a product, it is also kinder on the environment. It has been found to be responsibly and ethically made to help protect the fragile needs of the earth's eco-systems and is also safer and healthier for people to use and live with.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: <5g/L VOC's untinted (Volatile Organic Compounds contribute to atmospheric pollution). (Except Red base at 13.49 g/L)

The following descriptors have been adopted by APAS (Australian Paint Approval Scheme):

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

This product is classified as Very Low VOC* by the Australian Paint Approval Scheme. * Red base is Low VOC.

GREENTAG™ CERTIFICATION:

Porter's Eggshell Finish is certified with the Global GreenTag GreenRate™ Level A certification to Version 4.0 of the Global GreenTag International Product Certification Standard, under the certified name Porter's Paints.

A GreenRate Level A license is the highest ranking level in GreenTag's GreenRate™ program. As a result, Porter's Eggshell Finish receives the maximum recognition by the Green Building Council of Australia's Green Star® building rating tools' scheme. This level of recognition provides assurance to green building projects that Porter's Eggshell Finish demonstrates the maximum commitment to low toxicity, compliance to relevant social and environmental laws in the country of operation, fit for purpose certification and healthy VOC levels.

Recognition by green building rating tools for Porter's Eggshell Finish under a GreenRate® Level A certification include:

- Green Star®- Design & As Built v1.3 & Interiors v1.3 legacy tools for the 'Sustainable Products' credit.
- • Green Star® Performance rating tool for the 'Procurement and Purchasing: Refurbishment Materials' credit.
- • Green Star®- Building v1.0 tool – under the 'Responsible Product Framework' Porter's Eggshell Finish products may fall under any of the following credits depending on how and where they are used: Responsible Structure (Credit 6), Responsible Envelope (Credit 7), Responsible Finishes (Credit 9), Exposure to Toxins (Credit 13).
- ISCA's 'IS' rating tool (Infrastructure Sustainability in Australia and New Zealand).
- EC3's EarthCheck® Tourism and Hospitality project rating system.
- NZGBC's HomeStarNZ rating tool for Sustainable Product and Materials Calculator credits.
- Malaysian government's MyHIJAU® ecolabelling program
- Vietnam GBC's LOTUS® rating tool.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

COLOURS:

Choose from our large range of colours or ask one of our colourists for your own custom colour.

Very dark or deep coloured paints can sometimes exhibit light streaks when they are rubbed, touched or cleaned. This is commonly called "marring". Most marring disappears when gently wiped with a damp micro-fibre cloth.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On new unpainted timber, sand smooth and dust down, and apply 1 or 2 coats Porter's Prepare & Prime. Allow 2 hours dry time before overcoating.

On new unpainted plasterboard sheeting spot prime all joints then apply by brush, roller or spray 1 or 2 coats Porter's Prepare & Prime. Allow 2 hours dry time before overcoating.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Prepare & Prime. Allow 2 hours dry time before recoating or overcoating with top coat.

On bare masonry surfaces such as, render or brick, spot prime all repaired areas with Porter's Limeproof Undercoat Sealer, then apply 1 coat of same to entire area by brush, medium nap roller or spray. Touch dry in 1 hour. Allow 6 hours dry time before recoating or over-coating.

On bare metal surfaces use Porter's Universal Primer. Suitable for use as a metal primer, including galvanized iron, wrought iron, steel, aluminium, stainless steel, copper and brass. Universal Primer contains anti-corrosive pigments to inhibit rust and corrosion and a resin that delivers the extra adhesion required for metallic substrates. Please read the Universal Primer specification prior to use. Apply 1 or 2 coats. Touch dry in 20 minutes. Allow minimum 2 hours dry time between coats and 24 hours dry time before overcoating.

PREVIOUSLY PAINTED SUBSTRATES:

Provided the surface is clean and sound, Porter's Eggshell Finish is self-priming and can be applied directly over previously painted surfaces. (Except oil-based paints or polyurethanes).

All varnishes, polyurethanes or surfaces previously painted with oil-based enamel paint should be thoroughly sanded to remove gloss and to create a "keyed" surface. Loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Prepare & Prime, then apply one coat of same to entire area.

Allow 2 hours dry time before recoating or overcoating with top coat.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush, spray or a medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

COVERAGE RATES:

Covers approximately 12-14m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Prepare & Prime (coverage 12-14m² per litre).

Porter's Limeproof Undercoat Sealer (12m² per litre).

Porter's Universal Primer (coverage 10-12m² per litre).

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster before undercoating.

PACKAGING:

Porter's Eggshell Finish is available in 100ml Sample Pots, 500ml Test Pots, 1 litre, 2 litre, 4 litre, 10 litre & 15 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

WARRANTY:

15 YEAR GUARANTEE: Porter's Paints Eggshell Finish is guaranteed against peeling, flaking and blistering on external applications for 15 years if applied according to the specified instructions. This guarantee applies to residential work only and does not cover paint failure caused by any breakdown of coatings applied previously, where Porter's Paints Eggshell Finish is applied over coatings not specified by Porter's Paints or in the event of substrate failure. If the product does not perform as specified, we will replace the goods free of charge.

The warranty above applies for 15 years from the date of purchase. To make a claim under the warranty, please contact Porter's Paints using the details shown and provide details of your claim. You must

show proof of purchase and bear all expenses incurred in making a claim. The benefits of this warranty are in addition to other rights and remedies under any applicable law.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints

15 Gow St

Padstow NSW 2211

Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com

Porter's Paints

150 Hutt Park Rd

Gracefield

Lower Hutt 5010

New Zealand Ph: 0800 672 468