



## Product Specification

Product Name:

**PORTER'S BEESWAX**

---

### PRODUCT DESCRIPTION:

Porter's Beeswax is a fine beeswax polish designed to protect and enrich bare timber or painted surfaces. Buff to desired lustre.

### LOCATION:

Interior.

### SUGGESTED APPLICATIONS:

Can be applied as a protective finish over bare timber or painted surfaces.

### COLOUR:

Appears creamy white in can, dries clear.

### LIMITATIONS:

Please be aware that Porter's Beeswax may make the applied paint colour appear darker.

Not suitable for use in wet areas.

Do not apply in high humidity, below 10°C or above 30°C.

### PREPARATION:

Follow drying time instructions from the specification of the product you are coating.

### APPLICATION:

Apply sparingly with a soft lint free cloth or fine steel wool.

Ensure Beeswax is sparingly and evenly applied.

Before the wax is completely dry buff vigorously by hand with a soft clean cloth, or mechanically with a lamb's wool buffer.

### COVERAGE RATES:

Covers approximately 10-12m<sup>2</sup> per kg, depending upon porosity, surface texture and wastage rates.

### WASH UP:

Pure gum turpentine.

## **PACKAGING:**

Porter's Beeswax is available in 225g tins.

## **STORAGE:**

Store in a cool dry area, protected from frost.

## **PRECAUTIONS:**

Flammable liquid and vapour. Harmful if swallowed, in contact with skin and if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness and dizziness. Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation.

## **MANUFACTURER'S/DISTRIBUTOR'S DETAILS:**

Porter's Paints  
288 Coward St  
Mascot NSW 2020  
Australia  
Phone: (02) 9698-5322  
Toll free: 1800 656 664  
Fax: (02) 9699-5322  
E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)  
Web: [www.porterspains.com](http://www.porterspains.com)

Porter's Paints  
150 Hutt Park Rd  
Gracefield  
Lower Hutt 5010  
New Zealand  
Ph: 0800 672 468