



Product Specification

Product Name:

PORTER'S FRENCH WASH™

PRODUCT DESCRIPTION:

Porter's French Wash™ creates the look of delicate broken colour - a subtle marble-like finish. This elegant, timeless effect can be created by both the professional painter and the DIY home decorator, using Porter's two step French Wash™ system. French Wash™ can be ragged, rag rolled, dragged or sponged to produce a variety of painted effects. Step 1 is the application of Porter's Low Sheen Acrylic, tinted to an appropriate colour and used as a base. Step 2 is the application and ragging of the French Wash™ (usually tinted slightly darker) over the top of the Low Sheen Acrylic, creating the soft, broken colour effect.

LOCATION:

Interior.

ENVIRONMENTAL INFORMATION:

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum

performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding. On bare surfaces such as new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and

repaired areas with Porter's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

PREVIOUSLY PAINTED SUBSTRATES:

Provided the surface is clean and sound, Porter's Low Sheen Acrylic is self-priming and can be applied directly over previously painted surfaces.

Previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply one coat to entire area. Touch dry two hours. Allow 6 hours dry time.

APPLICATION:

STEP 1 – APPLICATION OF PORTER'S LOW SHEEN ACRYLIC:

Stir paint thoroughly prior to use. Apply two coats by brush, spray or a medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 18-24 hours dry time.

STEP 2 – APPLICATION OF FRENCH WASH:

(For non-professional painters, the application of French Wash™ is a two-person operation).

Starting at the top left hand corner of the wall the first person should apply French Wash™ using a wide brush (50-75mm) in a random pattern. It is

important that good coverage is achieved and there are no areas where the product is not completely applied. Following closely behind, the second person creates the desired pattern by ragging muslin cloth over the freshly painted French Wash™ surface, turning the cloth in your hand to avoid a "stamped" pattern and to use dry areas of cloth. The method we recommend is not to hold the muslin on the surface and roll, but to use a large amount (at least 5m) of scrunched muslin and "pounce" or press this quickly and repeatedly to the wall, absorbing the French Wash and leaving a broken, subtle pattern of colour. Care should be taken to leave a wet edge (at least 15cm wide) at all times. Do not go back over completed work. Do not stop in the middle of a wall. All work should be arranged to allow completion at a natural division such as a corner. Corners can be ragged by flicking the muslin into the corner.

Touch dry in 2 hours. Allow 6 hours dry time.

Please Note: Do not change roles during application as each person has an individual style or technique, and an inconsistent result will be very obvious on the wall.

If a second coat of French Wash™ is required (either in the same or a different colour), allow first coat 24 hours dry time.

Allow 72 hours dry time before applying any clear sealer (optional).

ADDITIONAL APPLICATION TIPS:

For a softer, more subtly aged look - just when the French Wash™ is nearly dry, use a dry flogger brush to lightly brush in all directions, breaking up darker areas and creating a very subtle colour variation.

For a more complex colour layered effect – multiple coats of French Wash™ in varying colours can be added, as long as the previous coat is completely dry.

Use the wall as your palette – use 2 or 3 French Wash™ colours at once, blending areas as you go.

COVERAGE RATES:

Porter's Low Sheen Acrylic covers approximately 12-14m² per litre, depending upon porosity, surface texture and wastage rates.

Porter's French Wash™ covers approximately 25m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Limeproof Undercoat Sealer (coverage 12m² per litre) is recommended where an undercoat/primer is required when preparing substrate for painting.

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster before undercoating.

Porter's Low Sheen is the only recommended base coat for use in conjunction with French Wash™. (Coverage 12-14m² per litre).

If extra protection is required for your French Wash™ finish we recommend the application of Porter's All Purpose Clear Sealer (coverage 15m² per litre).

PACKAGING:

Porter's Low Sheen Acrylic is available in 1 litre, 4 litre, 10 litre & 15 litre sizes.

Porter's French Wash™ is available in 500ml, 1 litre, 2 litre, 4 litre & 15 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
288 Coward St
Mascot NSW 2020
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: www.porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468