



## Product Specification

Product Name:

**PORTER'S MATT WALL SEALER**

---

### PRODUCT DESCRIPTION:

Porter's Matt Wall Sealer is an interior use product that is recommended as a protective clear sealer specifically designed for use over Porter's Interno, Porter's Interior Distemper, Porter's Lime Wash or Boncote Cement Paint (when used on a interior surface). Allows these surfaces to resist marking and staining, makes these matt decorative finishes wipeable.

When recoating Interno or Distemper that has been protected with Matt Wall Sealer, Matt Wall Sealer can be painted over directly without the need to begin again with an undercoat.

### LOCATION:

Interior.

### ENVIRONMENTAL INFORMATION:

This product contains: 9.67g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution).

The following descriptors have been adopted by APAS (Australian Paint Approval Scheme):

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

This product is classified as Low VOC by the Australian Paint Approval Scheme.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

### SUGGESTED APPLICATIONS:

Suitable for use as a protective clear sealer for use over Porter's Interno, Interior Distemper, Porter's Lime Wash and Boncote Cement Paint (interior) only.

### COLOUR:

Appears milky white in can, dries clear.

## LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C. Allow paints to cure for a minimum of 7 days before application. Over saturation whilst applying Matt Wall Sealer, or a substrate which is not completely dry, may cause white markings to appear on a surface. Avoid dribbles or runs as these will remain evident when dry. Test before use as a slight colour variation may occur.

## PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould. Dust down before proceeding. Allow all paints and finishes to dry a minimum of 7 days prior to the application of Porter's Matt Wall Sealer.

## APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush in a random or "crows feet" method. Touch dry in 2 hours. Allow minimum 6 hours dry time between coats. Allow to dry 6 hours.

## COVERAGE RATES:

Covers approximately 15m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

## WASH UP:

Water.

## PACKAGING:

Porter's Matt Wall Sealer is available in 1 litre, 4 litre & 15 litre sizes.

## STORAGE:

Store in a cool dry area, protected from frost.

## PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

## MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints  
288 Coward St  
Mascot NSW 2020  
Australia  
Phone: (02) 9698-5322  
Toll free: 1800 656 664  
Fax: (02) 9699-5322  
E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)  
Web: [www.porterspains.com](http://www.porterspains.com)

Porter's Paints  
150 Hutt Park Rd  
Gracefield  
Lower Hutt 5010  
New Zealand  
Ph: 0800 672 468