



Product Specification

PORTER'S REVIVE™ FURNITURE PAINT

PRODUCT DESCRIPTION:

Porter's Revive Furniture Paint™ delivers an elegant satin finish with hard-wearing protection for furniture, cabinetry, doors and other woodwork.

Modernise dated furniture, cover old scratches and marks, and revive your much-loved pieces for years of further use and enjoyment.

Porter's Revive is formulated with built-in wax infusion, which gives the paint a smoother, more durable finish, with no need for a finishing sealer or wax.

- Ultra smooth, self-levelling to reduce brush marks.
- Washable - most household marks and stains easily wipe away.
- For interior and exterior use.
- Superior colour depth.
- High coverage.
- Easy to clean and dust.
- Low odour.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: <1g/L VOC's untinted (Volatile Organic Compounds contribute to atmospheric pollution).

The following descriptors have been adopted by APAS (Australian Paint Approval Scheme):

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

This product is classified as Very Low VOC by the Australian Paint Approval Scheme.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Suitable for most surfaces, including bare, previously varnished, lacquered or painted furniture. Also suitable for doors, cabinetry, woodwork, skirting and trim.

COLOUR:

There are twelve popular colours, factory tinted and ready to go.

LIMITATIONS:

Not suitable for floor surfaces. Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

All pieces should be thoroughly cleaned to remove dust, dirt and grime, and if necessary, degreased. Lightly sand (see *Helpful Hint**) and wipe off dust with a damp cloth.

Optional – fill old holes and damaged areas with a wood putty, following the manufacturer's directions.

For best results, prime before painting. After sanding, apply 1 coat of Porter's Prepare & Prime (a multi-surfaces primer and stain blocker). Allow to dry for 2 hours before applying the topcoat.

**Helpful Hint:* The timber used for furniture can contain a lot of tannin (especially very old pieces), which can bleed through and stain the final paint coat. Leave as much of the existing finish as you can, just scuff or lightly de-gloss the surface so that the primer, can adhere.

PREPARING LAMINATE:

Step 1: Lightly sand the surface using 180 grit sandpaper to remove any sheen and create a key.

Step 2: Apply 2 coats of Dulux Precision® Maximum Strength Adhesion Primer, following the on-pack instructions. Allow 24 hours to dry and cure before overcoating with Porter's Revive.

APPLICATION:

Stir or shake the jar thoroughly before use.

First Coat:

Paint a thin coat in the direction of the grain of the wood, using long strokes. Paint from end to end. A microfibre roller can sometimes leave a subtle texture, which can be smoothed off by lightly dragging a

brush over at a low angle. Avoid short brush strokes, and repeatedly brush back over the paint as it is drying, as this will cause stop/start marks and brushstroke texture.

Touch dry in 1 hour. Allow a minimum of 2 hours dry time before applying the second coat.

Helpful Hint: Revive Furniture Paint is formulated to be self-levelling for a smoother finish, but despite that, it is still possible to create unwanted brush marks. The leading cause of brush marks is having too much paint loaded onto the brush. The brush should be dipped halfway up the bristles, and then the excess paint removed. Paint should be visible on the brush, but no paint should drip off.

Second Coat:

Inspect your project and gently sand off any drips. For a super smooth result, gently sand down any visible brushstrokes with a fine sandpaper sponge block. Wipe off any dust and apply a second coat as you did for the first coat, using long strokes and brushing from end to end to avoid start/stop marks.

Allow to dry for 8 hours. Full hardness takes around 7 days. Avoid very heavy use immediately after drying.

The built-in wax technology means there is no need to apply a final clear finish or wax.

COVERAGE RATES:

Covers approximately 12-14m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Prepare & Prime.

PACKAGING:

Porter's Revive™ Furniture Paint is available in 400ml jars.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints

15 Gow St

Padstow NSW 2211

Australia

Phone: (02) 9698-5322

Toll-free: 1800 656 664

Fax: (02) 9699-5322

NZ Customer Service: 0800 672 468

E-mail: enquiries@porters.com.au

Web: www.porterspains.com

Porter's Paints

150 Hutt Park Rd

Gracefield

Lower Hutt 5010

New Zealand

Ph: 0800 672 468

Dulux Precision® Maximum Strength

Adhesion Primer is a registered trademark of

Dulux Paints & Coatings.