



Product Specification

PORTER'S MATT WALL SEALER

PRODUCT DESCRIPTION:

Porter's Matt Wall Sealer is an interior use product that is recommended as a protective clear sealer specifically designed for use over Porter's Interno, Porter's Interior Distemper or Porter's Smooth Impasto. Porter's Matt Wall Sealer allows these surfaces to resist marking and staining, making these matt decorative finishes wipeable.

When recoating Interno, Interior Distemper or Smooth Impasto that has been protected with Matt Wall Sealer, Matt Wall Sealer can be painted over directly without the need to begin again with an undercoat.

LOCATION:

Interior.

ENVIRONMENTAL INFORMATION:

This product contains: 9.67g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution).

The following descriptors have been adopted by APAS (Australian Paint Approval Scheme):

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

This product is classified as Low VOC by the Australian Paint Approval Scheme.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Suitable for use as a protective clear sealer for use over Porter's Interno, Interior Distemper and Porter's Smooth Impasto.

COLOUR:

Appears milky white in can, dries clear.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C. Allow paints to cure for a minimum of 7 days before application. Over saturation whilst applying Matt Wall Sealer, or a substrate which is not completely dry, may cause white markings to appear on a surface. Avoid dribbles or runs as these will remain evident when dry. Test before use as a slight colour variation may occur.

PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould. Dust down before proceeding. Allow all paints and finishes to dry a minimum of 7 days prior to the application of Porter's Matt Wall Sealer.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush in a random or “crows feet” method. Touch dry in 2 hours. Allow a minimum 6 hours dry time between coats. Allow to dry 6 hours.

COVERAGE RATES:

Covers approximately 15m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

PACKAGING:

Porter's Matt Wall Sealer is available in 1 litre & 4 litre sizes.

STORAGE:

Store in a cool, dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

POST INSTALLATION MAINTENANCE SCHEDULE:

1.

On vertical surfaces previously coated with Matt wall sealer a periodic washdown with a dry microfibre cloth is recommended. Alternatively, for more stubborn dirt or grease, a water-dampened cloth with a

mild detergent or soap is okay. Do not let any horizontal surfaces that have been coated with Matt Wall Sealer to have dormant water, grease, oil or any other staining liquids or solids sit on the surface for extended periods, as this may migrate through the coating, making staining difficult to remove.

2.

If the Matt Wall Sealer needs a recoat, ensure the surface is free from oil or grease by cleaning with a mild solution of warm water and sugar soap on a dampened cloth. When dry, lightly sand with a P240 grade sandpaper to slightly de-gloss the surface and remove all dust and contaminants. Reapply Matt Wall Sealer as per the standard specification.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints

15 Gow St

Padstow NSW 2211

Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com

Porter's Paints

150 Hutt Park Rd

Gracefield

Lower Hutt 5010

New Zealand

Ph: 0800 672 468