



Product Specification

PORTER'S AQUA GLOSS ENAMEL

PRODUCT DESCRIPTION:

Porter's Aqua Gloss Enamel is a water based acrylic enamel that dries to a hardwearing finish that provides the benefits of an oil-based enamel with none of the drawbacks.

Self-levelling (to minimise brush marks), non-yellowing, tough wearing, long lasting with excellent gloss retention, easy to apply, low odour, fast drying with easy re-coat.

Excellent for exterior woodwork and trim areas as its high UV resistance ensures durability and longevity in a range of temperature and climatic conditions. Porter's Aqua Gloss Enamel resists peeling and flaking and is fully washable.

LOCATION:

Interior and exterior. Ideal for doors, architraves, windows and trim.

ENVIRONMENTAL INFORMATION:

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, metal, wood, masonry and previously painted surfaces.

COLOURS:

Choose from our large range of colours or ask our colourist for your own custom colour.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On new unpainted timber, sand smooth and dust down, and apply 1 or 2 coats Porter's Prepare & Prime. Allow 2 hours dry time before overcoating.

On new unpainted plasterboard sheeting spot prime all joints then apply by brush, roller or spray 1 or 2 coats Porter's Prepare & Prime. Allow 2 hours dry time before overcoating.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Prepare & Prime. Allow 2 hours dry time before recoating or overcoating with top coat.

On bare masonry surfaces such as, render or brick, spot prime all repaired areas with Porter's Limeproof Undercoat Sealer, then apply 1 coat of same to entire area by brush, medium nap roller or spray. Touch dry in 1 hour. Allow 6 hours dry time before recoating or over-coating.

On bare metal surfaces use Porter's Universal Primer. Suitable for use as a metal primer, including galvanized iron, wrought iron, steel, aluminum, stainless steel, copper and brass. Universal Primer contains anti-corrosive pigments to inhibit rust and corrosion and a resin that delivers the extra adhesion required for metallic substrates. Please read the Universal Primer specification prior to use. Apply 1 or 2 coats. Touch dry in 20 minutes. Allow minimum 2 hours dry time between coats and 24 hours dry time before overcoating.

PREVIOUSLY PAINTED SUBSTRATES:

When painting over a water-based acrylic paint, provided the surface is clean, sound and sanded to remove gloss, Porter's Aqua Gloss Enamel is self-priming and can be applied direct.

All varnishes, polyurethanes or surfaces previously painted with oil-based enamel paint should be thoroughly sanded to remove gloss and to create a "keyed" surface. Loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with either Porter's Prepare & Prime, then apply one coat of same to entire area. Allow 2 hours dry time before recoating or overcoating with top coat.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush, short nap roller or spray (fine finish spray tip*).

Touch dry in 1 hour. Allow minimum 2 hours dry time between coats.

Allow 8 hours dry time. Full paint hardness is achieved after 7 days, depending upon conditions.

*Recommendations:

HVLP Spray tip no. 3

Wagner®: F230 Aircoat (211 for architraves and trim and 411 for doors), pressure 1100 PSI.

Graco®: Air assisted airless (210 for architraves and trim, 410 for doors), pressure 1100PSI.

COVERAGE RATES:

Covers approximately 12-14m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Prepare & Prime (coverage 12-14m² per litre).

Porter's Limeproof Undercoat Sealer (12m² per litre).

Porter's Universal Primer (coverage 10-12m² per litre).

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster before undercoating.

PACKAGING:

Porter's Aqua Gloss Enamel is available in 1 litre & 4 litre sizes.

Standard base is also available in 10 litre.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

WARRANTY:

15 YEAR GUARANTEE: Porter's Paints Aqua Gloss Enamel is guaranteed against peeling, flaking and blistering on external applications for 15 years if applied according to the specified instructions. This guarantee applies to residential work only and does not cover paint failure caused by any breakdown of coatings applied previously, where Porter's Paints Aqua Gloss Enamel is applied over coatings not specified by Porter's Paints or in the event of substrate failure. If the product does not perform as specified, we will replace the goods free of charge.

The guarantee above applies for 15 years from the date of purchase. To make a claim under the guarantee, please contact Porter's Paints using the details shown and provide details of your claim. You must show proof of purchase and bear all expenses incurred in making a claim. The benefits of this guarantee are in addition to other rights and remedies under any applicable law.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

A Commercial Warranty is also available to trade painters. Please contact your Business Development Manager/Sales Representative should this be required.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
15 Gow Street
Padstow NSW 2211
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468

®Wagner is a registered trademark of J Wagner GmbH
®Graco is a registered trademark of Graco Minnesota Inc.