

Product Specification

PORTER'S LIQUID COPPER & PATINA GREEN

PRODUCT DESCRIPTION:

Porter's Liquid Copper and Patina Green are used together to recreate copper with the green patination of age. Suitable for almost any paintable surface, both interior and exterior, the oxidisation effect that the Patina Green has on the Liquid Copper allows you to create your own authentic aged copper lamp bases, candlesticks, mirror frames, walls and garden ornaments.

LOCATION:

Interior or exterior.

ENVIRONMENTAL INFORMATION:

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, plastic, metal, paper

mâché, masonry and previously painted surfaces.

COLOURS:

Available in standard Copper or choose Rich Copper.

LIMITATIONS:

Not suitable for "high traffic" surfaces such as hand rails, door knobs etc as continued touching of

the surface will remove green patina effect.

The green patina effect can be delicate, and the application of clear coats or finishes over the

green patina effect will remove some or all the finish, and this can leave the Liquid Copper visible

without the Patina Green finish. We recommend that Liquid Copper & Patina Green be left to

weather naturally.

On exterior surfaces, be mindful that green patina stains (caused by run-off) may appear on

adjacent surfaces.

Porter's Liquid Copper can be used on its own, without the application of Patina Green. Please

note that the copper particles will react to moisture and finger marks. On exterior applications a

subtle green pating will develop naturally over time. On interior applications, continued touching

of the copper surface can leave dark fingerprints.

Do not apply in high humidity, below 10°c or above 30°c.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and

mould. Dust down before proceeding. On bare surfaces such as new unpainted plasterboard

sheeting, or timber, spot prime all joints and repaired areas with Porter's Prepare & Prime, then

© 2021 Porter's Paints a division of DuluxGroup (Australia) Pty Ltd Porter's Liquid Copper & Patina Green Page 2 of 5

apply 1 or 2 coats of same to entire area. Touch dry 20 minutes. Allow 2 hours dry time before

overcoating.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried

completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20

minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Prepare &

Prime. Touch dry 20 minutes. Allow 2 hours dry time before overcoating.

On bare masonry surfaces such as, render or brick, spot prime all repaired areas with Porter's

Limeproof Undercoat Sealer, then apply 1 coat of same to entire area by brush, medium nap roller

or spray. Touch dry in 1 hour. Allow 6 hours dry time before recoating or over-coating.

On bare metallic surfaces, apply one to two coats of Porter's Universal Primer. Touch dry 2 hours.

Recoat 6 hours. Allow to dry 24 hours.

PREVIOUSLY PAINTED SUBTRATES:

Previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping

off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints

and repaired areas with Porter's Prepare & Prime, then apply 1 or 2 coats of same to entire area.

Touch dry 20 minutes. Allow 2 hours dry time before overcoating.

APPLICATION:

APPLYING LIQUID COPPER:

Stir thoroughly prior to use as this ensures an even distribution of copper particles. Apply two

coats by brush. Touch dry in 2 hours. Allow minimum 12 hours dry time between coats.

APPI YING PATINA GREEN:

Note: Please always wear rubber gloves and safety goggles.

When the second coat of Porter's Liquid Copper is touch dry*, lightly apply by brush one coat of

Porter's Patina Green. Patination and oxidization will begin to develop within hours and will

continue to increase over the next 12 hours. To increase intensity of green patina effect,

additional coats may be applied, however, please note that the green patina is delicate, and

brushing on further coats can remove or change the initial patination. Allow each application to

dry thoroughly (minimum 3 hours) before applying additional coats

© 2021 Porter's Paints a division of DuluxGroup (Australia) Pty Ltd Porter's Liquid Copper & Patina Green

*For best results apply Patina Green when Liquid Copper is touch dry, and it must be applied

within 12 hours of the Liquid Copper being touch dry. This is because the longer the Liquid Copper

is left to dry the harder the paint resins will become, and the Patina Green will take longer to

react with the copper particles.

Please Note: Liquid Copper treated with Patina Green is a chemical reaction. Individual results

may vary due to film thickness, methods used, time elapsed, ambient temperatures, substrate

etc.

COVERAGE RATES:

Porter's Liquid Copper covers approximately 6-8m² per litre, depending upon porosity, surface

texture and wastage rates.

Porter's Patina Green covers approximately 10m² per litre.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Prepare & Prime (coverage 12-14m² per litre).

Porter's Limeproof Undercoat Sealer (12m² per litre).

Porter's Universal Primer (coverage 10-12m² per litre.

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster

before undercoating.

PACKAGING:

Porter's Liquid Copper is available in 500ml, 1 litre & 4 litre sizes.

Porter's Patina Green is available in 500ml.

© 2021 Porter's Paints a division of DuluxGroup (Australia) Pty Ltd Porter's Liquid Copper & Patina Green Page 4 of 5

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

When applying Patina Green wear rubber gloves and safety goggles. Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate

 $ventilation. \ If \ accidental \ contact \ occurs, rinse \ immediately \ with \ water. \ Check \ colour \ before \ use.$

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints

15 Gow St

Padstow NSW 2211

Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspaints.com

Porter's Paints

150 Hutt Park Rd

Gracefield

Lower Hutt 5010

New Zealand

Ph: 0800 672 468